

# ULTRA LIFE

Longer life and 4 year guarantee



### 4 year OSRAM guarantee

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



### Extra lifetime

Up to four times longer lifetime compared to standard halogen lamps



### More durability

For longer replacement cycles and additional reliability and comfort



### The durable light with up to four times longer lifetime

OSRAM ULTRA LIFE automotive lamps are a favorite when it comes to durability. They have an impressive lifespan up to four times longer compared to standard halogen lamps and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). OSRAM provides a 4 year guarantee for the reliable ULTRA LIFE headlight lamps ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). In addition to this, ULTRA LIFE headlight lamps have a modern design with silver cap (H4/H7/H11). They are therefore ideal for frequent drivers or people who use daytime running lights, and can also be used in clear-glass headlights.

# Product family datasheet

## Technical data

Product description	Product information		Electrical data				Photometrical data
	Order reference	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminous flux
ULTRA LIFE H1 <sup>1)</sup>	64150ULT	Halogen headlight lamp	68 W <sup>4)</sup>	12.0 V	55.00 W	13.2 V	1550 lm
ULTRA LIFE H4 <sup>2)</sup>	64193ULT	Halogen headlight lamp	75 / 68 W <sup>4)</sup>	12.0 V	60/55 W	13.2 V	1650/1000 lm
ULTRA LIFE H7 <sup>3)</sup>	64210ULT	Halogen headlight lamp	58 W <sup>4)</sup>	12.0 V	55.00 W	13.2 V	1500 lm
ULTRA LIFE H11	64211ULT	Halogen headlight lamp	62 W <sup>4)</sup>	12.0 V	55.00 W	13.2 V	1350 lm

Product description	Luminous flux tolerance	Dimensions & weight	Lifespan		Capabilities	Certificates & standards
		Diameter	Lifespan B3	Lifespan Tc	Technology	ECE category
ULTRA LIFE H1 <sup>1)</sup>	±15 %	9 mm	1200 h	2000 h	HAL	H1
ULTRA LIFE H4 <sup>2)</sup>	±15 / ±15 %	17.0 mm	300 / 2000 h <sup>5)</sup>	700 / 3000 h <sup>5)</sup>	HAL	H4
ULTRA LIFE H7 <sup>3)</sup>	±10 %	12.0 mm	1000 h	1500 h	HAL	H7
ULTRA LIFE H11	±10 %	12.0 mm	1000 h	2000 h	HAL	H11

Product description	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
ULTRA LIFE H1 <sup>1)</sup>	05-03-2024	4008321416162   4008321416209   4008321416100   4052899412156   4052899412170   4052899987043   4062172257008   4052899425187   4062172388122   4062172395526	No declarable substances contained	In work
ULTRA LIFE H4 <sup>2)</sup>	05-03-2024	4008321416230   4008321416124   4008321416186   4008321421272   4052899031562   4052899513198   4062172250238   4052899425125   4052899425224   4062172387491   4062172395748	No declarable substances contained	In work

## Product family datasheet

Product description	Environmental information			
	Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
ULTRA LIFE H7 <sup>3)</sup>	10-05-2024	4050300879284   4008321416148   4008321416292   4008321416261   4008321421258   4052899131453   4052899436237   4052899436213   4052899436152   4052899436299   4052899436534   4052899436251   4052899436572   4052899436558   4052899476004   4052899513211   4062172250207   4008321416087   4062172387613   4062172395205	No declarable substances contained	In work
ULTRA LIFE H11	08-03-2024	4050300602387   4052899431164   4052899436114   4052899436138   4052899436510   4052899436190   4052899436473   4052899436176   4052899436275   4062172387736   4062172394635   4062172395267	No declarable substances contained	In work

<sup>1)</sup> Lamp complies with ECE R 37 and SAE (DOT) regulations

<sup>2)</sup> With silver cap







<sup>3)</sup> Lamp complies with ECE R 37 and SAE (DOT) regulations/With silver cap

<sup>4)</sup> Maximum

<sup>5)</sup> Filament 1

## Product family datasheet

### Download Data

File	
	Brochures 724901_ULTRA LIFE Leaflet EN
	Product movie 724899_ULTRA LIFE Trailer EN
	360 Degree Image ULTRA LIFE H1 64150ULT
	360 Degree Image ULTRA LIFE H4 64193ULT
	360 Degree Image ULTRA LIFE H7 64210ULT
	360 Degree Image ULTRA LIFE H11 64211ULT

### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

