

ULTRA LIFE PY21W

Up to four times longer lifetime



Extra lifetime

Up to four times longer lifetime compared to standard auxiliary lamps



More durability

For longer replacement cycles and additional reliability and comfort



Wide product range

Fits for most common auxiliary lamp types



The durable light with up to four times longer lifetime

With ULTRA LIFE, you choose durable signal lamps for your car. The lamps provide a long life span - up to four times longer lifetime compared to standard lamps - and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). They are therefore ideal for frequent drivers.

Product datasheet

Technical data

Product information

| | |
|---|----------------|
| Order reference | 7507ULT |
| Application (Category and Product specific) | Auxiliary lamp |


Electrical data

| | |
|-----------------------|---------|
| Power input | 25 W |
| Nominal voltage | 12.0 V |
| Nominal wattage | 21.00 W |
| Power input tolerance | ±6 % |
| Test voltage | 13.5 V |

Photometrical data

| | |
|-------------------------|--------|
| Luminous flux | 280 lm |
| Luminous flux tolerance | ±20 % |

Dimensions & weight



| | |
|----------------|---------|
| Length | 52.5 mm |
| Diameter | 25.0 mm |
| Product weight | 8.06 g |

Lifespan

| | |
|-------------|--------|
| Lifespan B3 | 500 h |
| Lifespan Tc | 1000 h |

Additional product data

| | |
|-----------------------------|---------------------------------|
| Base (standard designation) | BAU15s |
| Product remark | Amber lamp for clear indicators |

Product datasheet

Capabilities

| | |
|------------|-----|
| Technology | AUX |
|------------|-----|

Certificates & standards

| | |
|--------------|-------|
| ECE category | PY21W |
|--------------|-------|

Country specific categorizations

| | |
|-----------------|---------|
| Order reference | 7507ULT |
|-----------------|---------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|---|
| Date of Declaration | 05-03-2024 |
| Primary Article Identifier | 4008321413147 4008321415165 4062172394871 |
| Candidate List Substance 1 | No declarable substances contained |
| Declaration No. in SCIP database | In work |

Country specific information

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---------------|-------------|---------|------------|--------|
| 4008321413147 | OSRA7507ULT | - | - | - |
| 4008321413154 | OSRA7507ULT | - | - | - |
| 4008321413147 | OSRA7507ULT | - | - | - |


Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4008321413147 | ULTRA LIFE PY21W | Unpacked 1 | - x - x - | | |
| 4008321413154 | ULTRA LIFE PY21W | Folding carton box 10 | - x - x - | | |
| 4008321413161 | ULTRA LIFE PY21W | Shipping carton box 50 | 273 mm x 145 mm x 65 mm | 2.57 dm ³ | 553.00 g |
| 4008321415165 | ULTRA LIFE PY21W | Blister 2 | 135 mm x 95 mm x 26 mm | 0.33 dm ³ | 27.00 g |
| 4008321415172 | ULTRA LIFE PY21W | Shipping carton box 20 | 279 mm x 115 mm x 146 mm | 4.68 dm ³ | 361.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Download Data

| File | |
|---|--|
|  | 360 Degree Image ULTRA LIFE PY21W 7507ULT |

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM