

XENARC COOL BLUE BOOST

Hyper white light for LED look for off-road use



Xenon hyper white light for stylish LED look

Hyper white light due to a special filling system instead of conventional coating



Up to 7,000 K1)

High contrast and most stylish look



Enhanced brightness

More light allows to see farther and therefore react sooner



Hyper white light with up to 7,000 K for off-road use

XENARC COOL BLUE BOOST features hyper white xenon light for LED look and high color temperatures of up to 7,000 K. This is due to a special filling system instead of conventional coating. The lamps generate enhanced brightness. These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.1) Measured in headlamps

Product family datasheet

Technical data

| Product description | Electrical data | | | | | Photometrical data | Dimensions & weight |
|--|-----------------|-----------------|-----------------|-----------------------|--------------|--------------------|---------------------|
| | Power input | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Luminous flux | Length |
| XENARC COOL BLUE BOOST \pm D4S ¹⁾ | 35 W | 42.0 V | 35.00 W | ± 3 % | 13.5 V | 3200 lm | 77.3 mm |
| XENARC COOL BLUE BOOST \pm D3S ¹⁾ | 35 W | 42.0 V | 35.00 W | ± 3 % | 13.5 V | 3200 lm | 83.2 mm |
| XENARC COOL BLUE BOOST \pm D2S ¹⁾ | 35 W | 85.0 V | 35.00 W | ± 3 % | 13.5 V | 3200 lm | 77.3 mm |
| XENARC COOL BLUE BOOST \pm D1S ¹⁾ | 35 W | 85.0 V | 35.00 W | ± 3 % | 13.5 V | 3200 lm | 83.2 mm |

| Product description | Diameter | Lifespan | | Additional product data | Capabilities | Certificates & standards |
|--|----------|-------------|-------------|-----------------------------|--------------|--------------------------|
| | | Lifespan B3 | Lifespan Tc | Base (standard designation) | Technology | ECE category |
| XENARC COOL BLUE BOOST \pm D4S ¹⁾ | 9 mm | 1000 h | 1500 h | P32d-5 | HID | - ²⁾ |
| XENARC COOL BLUE BOOST \pm D3S ¹⁾ | 9 mm | 1000 h | 1500 h | PK32d-5 | HID | - ²⁾ |
| XENARC COOL BLUE BOOST \pm D2S ¹⁾ | 9 mm | 600 h | 1500 h | P32d-2 | HID | - ²⁾ |
| XENARC COOL BLUE BOOST \pm D1S ¹⁾ | 9 mm | 600 h | 1500 h | PK32d-2 | HID | - ²⁾ |

| Product description | Environmental information | | | |
|--|---|---|------------------------------------|--------------------------------------|
| | Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | | |
| Product description | Date of Declaration | Primary Article Identifier | Candidate List Substance 1 | Declaration No. in SCIP database |
| XENARC COOL BLUE BOOST \pm D4S ¹⁾ | 21-06-2024 | 4052899527522 4052899544871 4052899527546 | No declarable substances contained | In work |
| XENARC COOL BLUE BOOST \pm D3S ¹⁾ | 06-03-2024 | 4052899527560 4052899527584 4052899570467 4062172404181 | Lead | 339d84e0-b5c1-49b0-814c-94cae2e6e2fc |
| XENARC COOL BLUE BOOST \pm D2S ¹⁾ | 21-06-2024 | 4052899441026 4052899441064 4052899441040 4062172404150 | Lead | 6c57c564-b94d-41ad-aafc-6dd568694c25 |
| XENARC COOL BLUE BOOST \pm D1S ¹⁾ | 10-05-2024 | 4052899439207 4052899439184 4052899439221 4062172404129 | Lead | 4a196424-fbe4-4fd5-8eb2-6dfb70acf828 |

| Product description | CAS No. of substance 1 | Safe Use Instruction |
|--|------------------------|----------------------|
| XENARC COOL BLUE BOOST \pm D4S ¹⁾ | | |

Product family datasheet





| Product description | CAS No. of substance 1 | Safe Use Instruction |
|--|---------------------------|--|
| XENARC COOL BLUE BOOST \cong D3S ¹⁾ | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| XENARC COOL BLUE BOOST \cong D2S ¹⁾ | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| XENARC COOL BLUE BOOST \cong D1S ¹⁾ | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. |

¹⁾ Reduced UV emission/For projection headlights

²⁾ To be operated only with approved electronic control gear

Product family datasheet

Download Data

| File | |
|---|---|
|  | 360 Degree Image XENARC COOL BLUE BOOST OFFROAD D4S 66440CBB |
|  | 360 Degree Image XENARC COOL BLUE BOOST OFFROAD D3S 66340CBB |
|  | 360 Degree Image XENARC COOL BLUE BOOST OFFROAD D2S 66240CBB |
|  | 360 Degree Image XENARC COOL BLUE BOOST D1S 66140CBB |

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

This product must only be operated with approved electronic control gear.

Legal advice

*These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

