

FCS 64640 HLX 150W 24V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54263
Product Name	FCS 64640 HLX 150W 24V 40/CS 1/SKU
Application	Projector
LIF Code	A1/216
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	150 W
Nominal Voltage	24 V
Type of Current	AC

Light technical data

Luminous Flux	6000 lm
Light Center Length - LCL (in)	1.185 in
Light Center Length - LCL (mm)	30.1 mm
Color Temperature	3450 K
Color Rendering Index	100
Average Rated Life	50 h



Physical attributes

Base	G6.35
Bulb Shape	T3.25
Maximum Overall Length (in)	1.950 in
Maximum Overall Length (mm)	50 mm
Length l (in)	1.950 in
Length l (mm)	50 mm
Diameter d (in)	0.433 in
Diameter d (mm)	11.00 mm
Distance a (in)	1.185 in
Distance a (mm)	30.1 mm
Filament Dimensions Length (in)	0.1130 in
Filament Dimensions Length (mm)	2.9 mm
Filament Dimensions Width (in)	0.226 in
Filament Dimensions Width (mm)	5.8 mm

Additional product data

Product datasheet

Operating Position	s 90
---------------------------	------



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54263	4050300006727	Folding box (SKU)	1		
54263	4050300890647	Shipping box (Case)	40	5.9 in x 4.4 in x 4.6 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

- OSRAM does not accept liability for errors, changes and omissions.