

64258 20W 12V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54262
Product Name	64258 20W 12V 40/CS 1/SKU
Family Brand Name	XENOPHOT (HLX)
Application	Projector
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	20 W
Nominal Voltage	12 V
Type of Current	AC

Light technical data

Luminous Flux	350 lm
Light Center Length - LCL (in)	0.768 in
Light Center Length - LCL (mm)	19.5 mm
Color Temperature	3050 K
Color Rendering Index	100
Average Rated Life	2000 h



Physical attributes

Base	G4 BIPIN
Maximum Overall Length (in)	1.299 in
Maximum Overall Length (mm)	33 mm
Length l (in)	1.299 in
Length l (mm)	33 mm
Diameter d (in)	0.354 in
Diameter d (mm)	9.00 mm
Distance a (in)	0.768 in
Distance a (mm)	19.5 mm
Filament Dimensions Length (in)	0.0310 in
Filament Dimensions Length (mm)	0.8 mm
Filament Dimensions Width (in)	0.138 in
Filament Dimensions Width (mm)	3.5 mm

Additional product data

Operating Position	s90
--------------------	-----

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54262	4050300285153	Folding box (SKU)	1	1 in x 0.9 in x 2.8 in	
54262	4050300891019	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.