

## EJM 150W 21V 24/CS 1/SKU



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54747
Product Name	EJM 150W 21V 24/CS 1/SKU
Application	Projector - 8mm
Product Remark	- Lumens refers to screen lumens.

#### Electrical data

Nominal Wattage	150 W
Nominal Voltage	21 V
Type of Current	AC

#### Light technical data

Luminous Flux	170 lm
Working Distance a (in)	1.486 in
Working Distance a (mm)	38.1 mm
Color Temperature	3400 K
Color Rendering Index	100
Average Rated Life	40 h

#### Physical attributes

Base	GX5.3
Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length l (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	39.366 in
Diameter d (mm)	999.90 mm
Filament	C-8

#### Additional product data

Operating Position	Any
Lamp Type	MR16

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54747	0046135547478	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54747	10046135547475	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.