

## EKEX 150W 21V 24/CS 1/SKU



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

## Product datasheet

---

### Technical data

#### General product information

Product Number	58771
Product Name	EKEX 150W 21V 24/CS 1/SKU
Application	Projector - 8mm, Fiber-Optics
Product Remark	- Lumens refers to screen lumens.

#### Electrical data

Nominal Wattage	150 W
Nominal Voltage	21 V
Type of Current	AC

#### Light technical data

Luminous Flux	80 lm
Working Distance a (in)	1.75 in
Working Distance a (mm)	44.45 mm
Color Temperature	3150 K
Color Rendering Index	100
Average Rated Life	1000 h

#### Physical attributes

Base	GX5.3
Bulb Shape	MR16
Maximum Overall Length (in)	1.765 in
Maximum Overall Length (mm)	44.831 mm
Length l (in)	1.5 in
Length l (mm)	38.10 mm
Length l max. (in)	1.5 in
Length l max. (mm)	38.10 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	CC-8

#### Additional product data

Operating Position	Any
Lamp Type	MR16

---

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
58771	4052899513099	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
58771	4052899513105	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.