

20W 12V PAR36 CAP 12/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	55052
Product Name	20W 12V PAR36 CAP 12/CS 1/SKU
Application	Landscaping
Product Remark	- WFL=Wide Flood

Electrical data

Nominal Wattage	20 W
Nominal Voltage	12 V

Light technical data

Beam Angle (degree)	25
Centerbeam Candlepower (cp)	550
Color Rendering Index	100
Average Rated Life	4000 h

Physical attributes

Base	SCREW TERMINAL G53
Bulb Shape	PAR36
Maximum Overall Length (in)	2.75 in
Maximum Overall Length (mm)	69.850 mm
Length l (in)	2.75 in
Length l (mm)	69.850 mm
Diameter d (in)	4.500 in
Diameter d (mm)	114.30 mm
Filament	C-8

Additional product data

Operating Position	Any
Lamp Type	PAR36

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
55052	4008321470737	Folding box (SKU)	1	3.5 in x 3.5 in x 4.1 in	0.6 lb
55052	4008321470744	Shipping box (Case)	12	14.7 in x 11.1 in x 4.9 in	7.4 lb

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.