

HMI DIGITAL 1600W 1/CS 1/SKU



Product features and benefits

- Reduced flicker when used with high-speed electronic ballasts (up to 1000 Hz and higher)
- Suited for both analog and digital film productions
- High intensity light providing true color performance with a CRI>90
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- High energy efficiency providing up to 100 LPW
- Enhanced safety with UV-Stop (UVS) feature on all DIGITAL types

Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	56782
Product Name	HMI DIGITAL 1600W 1/CS 1/SKU
Family Brand Name	HMI DIGITAL

Electrical data

Nominal Wattage	1600 W
Nominal Voltage	155 V
Type of Current	AC

Light technical data

Luminous Flux	144000 lm
Light Center Length - LCL (mm)	85 mm
Color Temperature	7250 K
Color Rendering Index	92
Average Rated Life	750 h

Physical attributes

Base	G22 MEDIUM BIPOST
Maximum Overall Length (mm)	173 mm
Electrode Gap - cold (mm)	12,5 mm

Additional product data

Operating Position	Any
Hot Restart	Yes

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
56782	4062172294911	Shipping box (Case)	1	9.5 in x 6.1 in x 5.8 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.