

GLE 750W 115V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54523
Product Name	GLE 750W 115V 12/CS 1/SKU
Application	Stage & Studio

Electrical data

Nominal Wattage	750 W
Nominal Voltage	115 V
Type of Current	AC

Light technical data

Luminous Flux	17400 lm
Light Center Length - LCL (in)	2.359 in
Light Center Length - LCL (mm)	60.5 mm
Color Temperature	3050 K
Average Rated Life	1500 h

Physical attributes

Base	G9.5 MEDIUM BIPIN
Bulb Shape	T6
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l1 (in)	4.1 in
Length l1 (mm)	104 mm
Length l1 max. (in)	4.1 in
Length l1 max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.359 in
Distance a (mm)	60.5 mm
Filament	C-13D

Additional product data

Operating Position	Any
Lamp Type	SINGLE END

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
54523	4062172146517	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54523	4062172146524	Shipping box (Case)	12	7 in x 5.4 in x 6 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.