

# BTR 1000W 120V 12/CS 1/SKU



#### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

#### Technical data

## **General product information**

Product Number	54689		
Product Name	BTR 1000W 120V 12/CS 1/SKU  1,000 watt, tungsten halogen, medium to high voltage, single-ended		
General Description			
Application	STAGE & STUDIO		
Product Remark	- s (Operating Position) = Vertical, base down		

#### **Electrical data**

Nominal Wattage	1000 W
Nominal Voltage	120 V
Type of Current	AC

## Light technical data

Luminous Flux	27500 lm
Light Center Length - LCL (in)	2.165 in
Light Center Length - LCL (mm)	55.5 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	250 h

# Physical attributes

Base	P28s Medium Prefocus	
Bulb Shape	Т6	
Maximum Overall Length (in)	4.331 in	
Maximum Overall Length (mm)	110 mm	
Length I (in)	4.953 in	
Length I (mm)	127 mm	
Length l max. (in)	4.953 in	
Length l max. (mm)	127 mm	
Diameter d (in)	0.787 in	
Diameter d (mm)	20.00 mm	
Distance a (in)	2.165 in	
Distance a (mm)	55.5 mm	
Filament	C-13D	

## Additional product data

## Product datasheet

Operating Position	S 90
Lamp Type	SINGLE END

#### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54689	4062172147170	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.3 lb
54689	4062172147187	Shipping box (Case)	12	7 in x 5.4 in x 6 in	3.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.