

93728 HPL 575W 230V 12/CS 1/SKU



Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54618
Product Name	93728 HPL 575W 230V 12/CS 1/SKU
Family Brand Name	HPL
Application	Stage & Studio
Product Remark	- Lamp also available in 240 V model.

Electrical data

Nominal Wattage	575 W
Nominal Voltage	230 V
Type of Current	AC

Light technical data

Luminous Flux	14900 lm
Light Center Length - LCL (in)	2.352 in
Light Center Length - LCL (mm)	60.3 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	400 h

Physical attributes

Base	G9.5 W/HSINK
Bulb Shape	T19
Maximum Overall Length (in)	4.1 in
Maximum Overall Length (mm)	104 mm
Length l (in)	4.1 in
Length l (mm)	104 mm
Length l max. (in)	4.1 in
Length l max. (mm)	104 mm
Diameter d (in)	0.748 in
Diameter d (mm)	19.00 mm
Distance a (in)	2.352 in
Distance a (mm)	60.3 mm
Filament	6-C8

Additional product data

Operating Position	Any
--------------------	-----

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54618	4050300461816	Folding box (SKU)	1	1.6 in x 1.6 in x 5.1 in	0.2 lb
54618	4050300461823	Shipping box (Case)	12	6.9 in x 5.2 in x 5.7 in	2.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.