



## Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

## Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

# Product datasheet

## Technical data

### General product information

Application	Stage & Studio
-------------	----------------

### Electrical data

Nominal Wattage	235 W
Nominal Voltage	230 V
Type of Current	AC

### Light technical data

Luminous Flux	5100 lm
Light Center Length - LCL (in)	1.26 in
Light Center Length - LCL (mm)	32 mm
Color Temperature	3100 K
Color Rendering Index	100
Average Rated Life	100 h

### Physical attributes

Base	G5.3 BIPIN
Bulb Shape	T12
Maximum Overall Length (in)	2.20 in
Maximum Overall Length (mm)	55.9 mm
Length l (in)	2.20 in
Length l (mm)	55.9 mm
Diameter d (in)	0.500 in
Diameter d (mm)	12.70 mm
Distance a (in)	1.260 in
Distance a (mm)	32 mm

### Additional product data

Operating Position	Any
Lamp Type	SINGLE END

## Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	0046135544606	Folding box (SKU)	1		
	10046135544603	Shipping box (Case)	24	8.3 in x 5.6 in x 4.5 in	1.8 lb

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.