

## FSX 400W 230V 24/CS 1/SKU



### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift

### Areas of application

- Stage and theatre
- Studio, TV and film
- Professional Photography
- Club & Disco

## Product datasheet

### Technical data

#### General product information

Product Number	54897
Product Name	FSX 400W 230V 24/CS 1/SKU
Application	Projector
Product Remark	<ul style="list-style-type: none"><li>- Lamp has internal proximity reflector.</li><li>- s (Operating Position) = Vertical, base down</li></ul>

#### Electrical data

Nominal Wattage	400 W
Nominal Voltage	230 V
Type of Current	AC

#### Light technical data

Light Center Length - LCL (in)	1.424 in
Light Center Length - LCL (mm)	36.5 mm
Color Temperature	3200 K
Color Rendering Index	100
Average Rated Life	75 h

#### Physical attributes

Base	GY9.5
Bulb Shape	T6
Maximum Overall Length (in)	3.003 in
Maximum Overall Length (mm)	77 mm
Length l (in)	3.003 in
Length l (mm)	77 mm
Length l max. (in)	3.003 in
Length l max. (mm)	77 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Distance a (in)	1.424 in
Distance a (mm)	36.5 mm
Filament	C-13D
Filament Dimensions Length (in)	0.4760 in
Filament Dimensions Length (mm)	12.2 mm
Filament Dimensions Width (in)	0.417 in
Filament Dimensions Width (mm)	10.7 mm

## Product datasheet

### Additional product data

Operating Position	s 90
Lamp Type	SINGLE END

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54897	4008321484437	Folding box (SKU)	1	1.3 in x 1.3 in x 3.5 in	0.1 lb
54897	4008321484444	Shipping box (Case)	24	8.3 in x 5.6 in x 4.5 in	2.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.