

6.6A 105W MR16 64339C 20/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistence to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield lighting

Product datasheet

Technical data

General product information

Product Number	58963	
Product Name	6.6A 105W MR16 64339C 20/CS 1/SKU	
Application	Airfield/Airport	
Product Remark	- Male contacts according to DIN 46248.	

Electrical data

Nominal Wattage	105 W	
Current (A)	6.6 A	
Type of Current	AC	

Light technical data

Luminous Intensity (cd)	32000 cd	
Average Rated Life	1000 h	

Physical attributes

Base	LEADS W/MALE FLAT CONNECTORS
Bulb Shape	REFLECTOR
Maximum Overall Length (in)	1.890 in
Maximum Overall Length (mm)	48 mm
Diameter d (in)	1.984 in
Diameter d (mm)	50.40 mm

Additional product data

Operating Position	Any	
Lamp Type	SINGLE ENDED	

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58963	4008321105486	Folding box (SKU)	1	1.9 in x 1.9 in x 2.4 in	0.1 lb
58963	4008321105493	Shipping box (Case)	20	10.1 in x 4.3 in x 5.2 in	1.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

OSRAM does not accept liability for errors, changes and omissions.