

6.6A/40MR11/64333A 20/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield lighting

Product datasheet

Technical data

General product information

Product Number	58899
Product Name	6.6A/40MR11/64333A 20/CS 1/SKU
Application	Airfield/Airport

Electrical data

Nominal Wattage	40 W
Current (A)	6.6 A
Type of Current	AC

Light technical data

Luminous Intensity (cd)	12700 cd
Color Rendering Index	100
Average Rated Life	1500 h

Physical attributes

Base	LEADS W/FEMALE FLAT CONNECTORS
Bulb Shape	MR35
Maximum Overall Length (in)	1.45 in
Maximum Overall Length (mm)	37 mm
Diameter d (in)	1.390 in
Diameter d (mm)	35.30 mm

Additional product data

Operating Position	Any
Lamp Type	SINGLE ENDED

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58899	4008321166340	Folding box (SKU)	1	1.3 in x 1.3 in x 2 in	0.1 lb
58899	4008321166357	Shipping box (Case)	20	7.5 in x 3.2 in x 5.2 in	1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.