

6.6A150T4Q64354EWRDL 12/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield lighting

Product datasheet

Technical data

General product information

Product Number	58855
Product Name	6.6A150T4Q64354EWRDL 12/CS 1/SKU
Application	Airfield/Airport
Product Remark	- This lamp type is twice the life of the ANSI standard version.

Electrical data

Nominal Wattage	150 W
Current (A)	6.6 A
Type of Current	AC

Light technical data

Light Center Length - LCL (in)	1.54 in
Light Center Length - LCL (mm)	39.1 mm
Average Rated Life	1500 h

Physical attributes

Base	GY9.5
Maximum Overall Length (in)	2.56 in
Maximum Overall Length (mm)	65 mm
Diameter d (in)	0.531 in
Diameter d (mm)	13.50 mm
Filament	C Bar 6
Filament Dimensions Length (in)	0.2170 in
Filament Dimensions Length (mm)	5.5 mm
Filament Dimensions Width (in)	0.173 in
Filament Dimensions Width (mm)	4.4 mm

Additional product data

Operating Position	s90
--------------------	-----

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58855	4008321100207	Folding box (SKU)	1	1.7 in x 1.7 in x 4.4 in	0.1 lb
58855	10046135588553	Shipping box (Case)	12	7.1 in x 5.5 in x 5 in	0.8 lb

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
----------------	---------	-----------	----------	------------------------------	--------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.