

XBO 4000W/DHP L 1/CS 1/SKU



Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

Areas of application

- Digital Projection
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	69049			
Product Name	XBO 4000W/DHP L 1/CS 1/SKU			
Family Brand Name	XBO			
Application	Digital Cinema Projection			
Product Remark	 OFR=Ozone Free s (Operating Position) = Vertical, base down p (Operating Position) = Horizontal This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. 			

Electrical data

Nominal Wattage	4200 W
Nominal Voltage	33 V
Current (A)	128 A
Current Control Range (A)	95-137 A
Type of Current	DC

Light technical data

Light Center Length - LCL (mm)	123 mm
Average Rated Life	1300 h
Warranty Hours (hr)	1300 hrs
Service Warranty Lifetime (hr)	1500 hrs

Physical attributes

Base Anode	SFaX27-14x71		
Base Cathode	SFc27-16/55		
Bulb Shape	T60		
Maximum Overall Length (mm)	345 mm		
Length l1 max. (mm)	345 mm		
Diameter d (in)	2.362 in		
Diameter d (mm)	60.00 mm		
Distance a (mm)	123 mm		
Electrode Gap - cold (mm)	6.2 mm		

Additional product data

Product datasheet

Maximum Base Temperature (°C)	230 C
Cooling	Required

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69049	4062172030403	Shipping box (Case)	1	19.7 in x 8 in x 8 in	3.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.