

## GFT95DL/2G11/SE/OF 10/CS 1/SKU



### Product features and benefits

- Effective and environment-friendly disinfection without chemicals
- High UV-C radiance at 254 nm
- Low mercury content
- Long lifetime due to special coating
- Ozone-free

### Areas of application

- Air
- Water Purification
- Surface Sterilization

## Product datasheet

### Technical data

#### General product information

Product Number	23403
Product Name	GFT95DL/2G11/SE/OF 10/CS 1/SKU
Family Brand Name	Puritec
Application	Air and water purification, surface disinfection

#### Electrical data

Nominal Wattage	95 W
Nominal Voltage	115 V
Current (A)	0.80 A

#### Light technical data

Average Rated Life	9000 h
--------------------	--------

#### Physical attributes

Base	2G11
Bulb Shape	T17,5
Length l (mm)	530 mm
Diameter d (mm)	40 mm
Distance a (mm)	500 mm

#### Additional product data

Operating Position	Any
--------------------	-----

### Safety advice

To prevent possible serious injury, eyes and skin should not be exposed to direct or reflected ultraviolet light emitted by this lamp. This lamp is in Risk Group 3 per ANSI/IESNARP-27.3-96. Adequate protection should be provided by clothing, gloves, opaque materials, and ordinary window glass. Although this lamp will operate in standard fluorescent fixtures, it should not be used for general lighting applications.

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
23403	4052899012509	Folding box (SKU)	1	1.8 in x 1 in x 22.2 in	0.4 lb
23403	4052899012516	Shipping box (Case)	10	5.4 in x 4.1 in x 22.8 in	4.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.