

# XBO 3000W/HPS 1/CS 1/SKU



### Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

## Areas of application

- Digital Projection
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

# Product datasheet

### Technical data

## **General product information**

Product Number	69487			
Product Name	XBO 3000W/HPS 1/CS 1/SKU			
Family Brand Name	XBO			
Application	Digital Cinema Projection			
Product Remark	<ul> <li>OFR=Ozone Free</li> <li>s (Operating Position) = Vertical, base down</li> <li>p (Operating Position) = Horizontal</li> <li>This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.</li> </ul>			

### **Electrical data**

Nominal Wattage	3000 W
Nominal Voltage	29 V
Current (A)	105 A
Current Control Range (A)	60-112 A
Type of Current	DC

## \_ Light technical data

Light Center Length - LCL (mm)	128 mm
Color Temperature	6000 K
Average Rated Life	1000 h
Warranty Hours (hr)	1000 hrs
Service Warranty Lifetime (hr)	1300 hrs

# Physical attributes

Base Anode	SFaX30-14/83		
Base Cathode	SFc30-20/60		
Bulb Shape	T17		
Maximum Overall Length (mm)	334 mm		
Length l1 max. (mm)	334 mm		
Diameter d (in)	2.165 in		
Diameter d (mm)	55.00 mm		
Distance a (mm)	128 mm		
Electrode Gap - cold (mm)	4.4 mm		

## Additional product data

## Product datasheet

Operating Position	s15 p15
Maximum Base Temperature (°C)	230 C
Cooling	Required

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69487	4062172030335	Shipping box (Case)	1	19.7 in x 8 in x 8 in	3.1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.