

XBO 2000W/H XL 1/CS 1/SKU



Product features and benefits

- High luminance (point source)
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart
- Long lamp life with eXtreme Life technology

Areas of application

- Digital
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

Product datasheet

Technical data

General product information

Product Number	69477	
Product Name	XBO 2000W/H XL 1/CS 1/SKU	
Application	Cinema Film Projection	
Product Remark	 OFR=Ozone Free s (Operating Position) = Vertical, base down p (Operating Position) = Horizontal This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. XL=Xtreme Life 	

Electrical data

Nominal Wattage	2000 W
Nominal Voltage	26 V
Current (A)	70 A
Current Control Range (A)	50-85 A
Type of Current	DC

Light technical data

Light Center Length - LCL (mm)	142.5 mm	
Average Rated Life	3500 h	
Warranty Hours (hr)	3500 hrs	

Physical attributes

Base Anode	SFaX27-10
Base Cathode	SFaX27-12
Maximum Overall Length (mm)	370 mm
Length l1 max. (mm)	370 mm
Diameter d (in)	2.047 in
Diameter d (mm)	52.00 mm
Distance a (mm)	142.5 mm
Electrode Gap - cold (mm)	5.8 mm

Additional product data

Operating Position	s15 p15
Maximum Base Temperature (°C)	230 C
Cooling	Required

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69477	4008321211781	Shipping box (Case)	1	23.2 in x 9.2 in x 9 in	3.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.