


# LEDDriving FL H8/H11/H16

LED replacement for conventional fog lamps



**Cool White color temperature of 6,000 K**

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



**Superior brightness**

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



**Ultra compact LED replacement for conventional H8 H11 and H16 fog lamps as socket solution**

Easy installation with optimized compatibility

## Product datasheet



### New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps: With its ultra compact dimensions, the OSRAM LEDriving FL provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. These LED products offer a perfect color match with xenon and LED headlights and are for conventional H8, H11 and H16 fog lamps. A pair of new LEDriving FL lamps, comes with a 3-year OSRAM guarantee as well as with a long service life by less energy consumption. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

# Product datasheet

## Technical data

### Product information

Order reference	67219CW
Product type (off-road vs. on-road)	Off-road $\pm$ H8/H11/H16
Application (Category and Product specific)	Mainly used for headlight/ fog light applications


### Electrical data

Power input	9.02 W
Test voltage	13.5 V
Power input tolerance	$\pm 10$ %
Nominal wattage	8.20 W
Nominal voltage	12.0 V

### Photometrical data

Color temperature	6000 K
Luminous flux	720 lm
Luminous flux tolerance	$\pm 15$ %
Light color LED	Cool white

### Dimensions & weight



Product weight	32.90 g
Length	68.3 mm
Diameter	17.2 mm

### Lifespan

Lifespan Tc	5000 h
Guarantee	3 years
Lifespan B3	2500 h

## Product datasheet

### Additional product data

Base (standard designation)	PGJ19-1/2/3
-----------------------------	-------------

### Capabilities

Technology	LED
------------	-----

### Country specific categorizations

Order reference	67219CW
-----------------	---------

### Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899605046   4062172033312   4059089349544   4059089376885   4062172401890
Declaration No. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899605046	LEDDriving FL $\triangle$ H8/H11/H16	Folding carton box 2	136 mm x 56 mm x 161 mm	1.23 dm <sup>3</sup>	143.00 g
4052899605053	LEDDriving FL $\triangle$ H8/H11/H16	Shipping carton box 8	240 mm x 148 mm x 182 mm	6.46 dm <sup>3</sup>	696.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDDriving Retrofits - Exchange overview (EN)

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Detailed guarantee terms can be found at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

## Product datasheet

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM