Product family datasheet

OSRAM

LEDriving HL EASY XEN D5S



Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



Compact LED replacement for conventional D5S high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect

OSRAM's first Plug & Play off-road LED replacement for HID

With up to +180% more brightness1) the OSRAM LEDriving HL EASY XEN ensures a compact LED replacement of conventional D5S high and low beam lamps. These LED retrofit lamps are 12V compatible, come with a color temperature of 6,000 K and ensure a broader light distribution: more light1) allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling - a high speed fan provides maximized heat dissipation for more powerful performances. Premium OSRAM guality and LED technology grant a long lifetime.Please note: OSRAM LEDriving HL EASY XEN change is recommended to be carried out by a professional.1) compared to minimum ECE R98These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

LEDriving HL EASY XEN \doteq D5S

Technical data

| | Product information | | | General Product Information | Electrical | Electrical Data | |
|--|---|---|-----------------------------|--------------------------------|-------------------------------|-------------------------------------|--|
| Product description | Product type (off- road vs. on-road) | | n (Category ct specific) | Global order reference | Power input | Nominal voltage | |
| LEDriving HL EASY XEN ≜ D5S | Off-road ≙ D5S | Mainly use Beam, Hig | | 66540DWESY | 50 W | 12.0 V | |
| | | | | Photometric Data | | Physical Attributes & Dimensions | |
| Product description | Nominal wattage | | Test voltage | Nominal luminous flux | Luminous flux tolerance | Diameter | |
| LEDriving HL EASY XEN \triangleq D5S | 50 W | | 13.2 V | 5000 lm | ±25 % | 13.8 mm | |
| | Lifetime Data | e Capabilities Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | | |
| Product description | Lifespan Tc | Technology | Primary a identifier | | date list ance 1 | Declaration no. in SCIP database | |

4062172410298

No declarable

substances contained

No declarable

substances contained

5000 hr LED

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



