# **OSRAM**

# **BATTERYcharge SOLAR 20W**





### Works In overcast conditions

Doesn't require direct sunlight to provide power



### USB-A and USB-C charging

Remotely charge your devices such as phones, tablets and power banks



### IP65 water resistance

Designed to handle outdoor conditions with ease



## Compact, Foldable Solar Panel for independent charging of devices

The OSRAM BATTERYcharge SOLAR 20W is a compact, foldable solar panel designed to keep your devices powered off-grid. Featuring mono-crystalline solar panels in a robust, water-resistant case (IP65), it delivers up to 20W of free solar power, perfect for charging phones, tablets, and laptops via USB-C and USB-A ports (5V, 2.4A). Lightweight at just 0.8kg, it unfolds in seconds with an integrated stand for optimal sun exposure. The LED indicator confirms charging status, and it performs even in overcast conditions. Easy to use, durable, and built for adventure, it's the ideal travel companion for camping, hiking, and off-grid power.

### Product family datasheet

### Technical data

**Product description** 

BATTERYcharge SOLAR 20W

	Product information	General Product Information	Electrical Data	
Product description	Application (Category and Product specific)	Global order reference	Min battery capacity	Max battery capacity
BATTERYcharge SOLAR 20W	Solar battery maintainer	OFSP20	n/a	N/A Ah
			Physical Attributes & Dimensions	
Product description	Maintainance Charge (up to)	Charge Rate (Up to)	Height	Width
BATTERYcharge SOLAR 20W	2.4 A	N/A	263.0 mm	28.0 mm
		Dimensions & weight		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
BATTERYcharge SOLAR 20W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3eb402b7-f3de- 4565-bdb4- b62e962b88c9

2.2 m

**Power Cable Length** 

**Clamps Cable Length** 

N/A

Candidate list substance 1

Lead

Length

203.0 mm

### Product family datasheet

### **Application advice**

For more detailed application information and graphics please see product datasheet.

### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.