Product family datasheet

LEDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Cool White



Replaces conventional P21W lamps Easy upgrade to LED technology with

plug & play solutions



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Product information	Product information		General Product Information		Electrical Data	
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference		Power input	Nominal voltage	
LEDriving SL ≜ P21W	Mainly used for signal/ indicator applications	Off-road ≙ P21W	7506D\	WP	1.8 W	12 V	
			Photometric Data			Physical Attributes & Dimensions	
Product description	Nominal wattage	Test voltage	Nominal luminous flux		Luminous flux tolerance	Diameter	
LEDriving SL \doteq P21W	1 W	13.5 V	160 lm		±25 %	25.0 mm	
		Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Diameter		Lifespan Tc	Technology	Primary ar identifier	ticle	
LEDriving SL \doteq P21W	25.0 mm	1500 hr	4000 hr	LED ¹⁾	40621723 40621721	•	

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≙ P21W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4b523b49-273b- 43fa-a900- dfef06fdea31 e75f732e-151e- 4392-9807- f15711d460b4 cbc40782-6f5e-4a73- ad3f-4f03b28c1891 431a14a2-e6f5-451f- b379-4763b7bc7850

 $^{1)}$ Light-emitting diode lamp

4062172401210 | 4062172408318

Product family datasheet

Download Data

File
User instruction GPRS_Safety symbols instructions
Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.