

LEDDriving SL PY21W

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional PY21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for PY21W

LEDDriving SL PY21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional PY21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | | Electrical data | | |
|----------------------------------|---------------------|-------------------------------------|--|-----------------|-----------------|-----------------|
| | Order reference | Product type (off-road vs. on-road) | Application (Category and Product specific) | Power input | Nominal voltage | Nominal wattage |
| LEDDriving SL \triangleq PY21W | 7507DYP | Off-road \triangleq PY21W | Mainly used for signal/ indicator applications | 1.5 W | 12.0 V | 1.30 W |

| Product description | Power input tolerance | Test voltage | Photometrical data | Dimensions & weight | | Lifespan | |
|----------------------------------|-----------------------|--------------|--------------------|---------------------|----------|-------------|-------------|
| | | | Luminous flux | Length | Diameter | Lifespan B3 | Lifespan Tc |
| LEDDriving SL \triangleq PY21W | ± 10 % | 13.5 V | 50 lm | 52.5 mm | 25.0 mm | 1500 h | 4000 h |


| Product description | Additional product data | Capabilities | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|----------------------------------|-----------------------------|-------------------|--|----------------------------------|
| | Base (standard designation) | Technology | Date of Declaration | Primary Article Identifier |
| LEDDriving SL \triangleq PY21W | BAU15s | LED ¹⁾ | 07-03-2024 | 4062172152242 4062172401517 |

| Product description | Candidate List Substance 1 | CAS No. of substance 1 | Safe Use Instruction | Declaration No. in SCIP database |
|----------------------------------|----------------------------|------------------------|--|--------------------------------------|
| LEDDriving SL \triangleq PY21W | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | bcf00c1f-4751-4bd7-8ce1-efa17d78d8a9 |

¹⁾ Light-emitting diode lamp

Product family datasheet

Download Data

| File | |
|---|---|
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.