

# TYREinflate 450



### Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 3.5 minutes\*\*



### Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



### LED Light

Easy to operate even in darkness and in low light conditions



### Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 450 can inflate a tyre from flat in 3.5 minutes\*\*. Comes with auto stop feature to accurately get the desired pressure for your tyre. Includes a backlit digital display and white LED light for optimal illumination in darkness. The Tyreinflate 450's flat, solid design makes the unit stable whilst in use, as well as the wind up cable eliminating any messy wires and helping you get back on the road faster. Comes complete with three piece adaptor kit for bicycle tyres, balls and other inflatables.\*\*based on inflating a 13" tyre from flat to 2.41 BAR

## Product family datasheet

### Technical data

	General Product Information	Electrical Data	Physical Attributes & Dimensions	
Product description	Global order reference	Nominal voltage	Length	Width
TYRE inflate 450	OTI450	11.1 V	197.0 mm	88.0 mm










		Operating Conditions	Additional product data	Capabilities
Product description	Height	Noise Level (dB)	Display Type	Fuse
TYRE inflate 450	180.0 mm	90 dB	Digital	10 A

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Date of declaration	Candidate list substance 1	CAS No. of substance 1	Safe use instruction
TYRE inflate 450	23-10-2024	Lead	7439-92-1	Identiferingen av ämnet på kandidatlistan är tillräcklig för att artikeln ska kunna användas på ett säkert sätt.

Product description	Declaration no. in SCIP database
TYRE inflate 450	dda41c6e-d521-4522-a227-e170d9cf4d66

## Product family datasheet

### Download Data

File	
	User instruction TYREinflate 450
	Movie application TyreInflate How to Video (RU)
	Product movie TyreInflate 450 Product Video (EN)
	Product movie TyreInflate 450 Product Video (RU)
	Product movie TyreInflate How to Video (EN)
	Product movie TyreInflate How to Video (IT)
	Product movie TyreInflate 450 Product Video (ITA)
	Video OSRAM TYREinflate 450: Rapid tyre inflator with wind-up cable, LED light and digital display
	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

#### Safety advice

Product won't exceed noise levels of more than 90 dB

#### Legal advice

CE and EAC compliant

\* for precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

\*\* based on inflating a 13" tyre from flat to 2.41 BAR

Application advice:  
For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.