


NIGHT BREAKER 220 H4

Brightest OSRAM halogen light



Up to 220% more brightness

More light allows to see farther and therefore react sooner compared to the minimum legal standard




Up to 150m long beam

Better visibility



Gold cap

Modern look



The most powerful halogen light from OSRAM

Enter the next light level: With NIGHT BREAKER 220 – the brightest halogen automotive light from OSRAM! These cutting-edge headlight lamps impress with up to 220% more brightness and up to 20% whiter light compared to the minimum legal standard and generate an up to 150m long beam. More light and improved visibility can help drivers identify and react to traffic hazards more quickly. The ideal lamp for drivers who appreciate the difference that powerful automotive lighting makes. Available in H4 and H7 with a new gold cap.

Product datasheet

Technical data

Product information

| | |
|---|------------------------|
| Order reference | 64193NB220 |
| Product type (off-road vs. on-road) | On-road |
| Application (Category and Product specific) | Halogen headlight lamp |

Electrical data


| | |
|-----------------|-------------------------|
| Power input | 75 / 68 W ¹⁾ |
| Nominal voltage | 12.0 V |
| Nominal wattage | 60/55 W |
| Test voltage | 13.2 V |

¹⁾ Maximum

Photometrical data

| | |
|-------------------------|--------------|
| Luminous flux | 1650/1000 lm |
| Luminous flux tolerance | ±12 / ±15 % |

Dimensions & weight



| | |
|----------------|---------|
| Diameter | 13.0 mm |
| Product weight | 21.30 g |
| Length | 82.0 mm |

Lifespan

| | |
|-------------|---------------------------|
| Lifespan B3 | 80 / 200 h ¹⁾ |
| Lifespan Tc | 160 / 400 h ¹⁾ |

¹⁾ Filament 1 / Filament 2

Additional product data

Product datasheet

| | |
|-----------------------------|------|
| Base (standard designation) | P43t |
|-----------------------------|------|

Capabilities

| | |
|------------|-------------------|
| Technology | HAL ¹⁾ |
|------------|-------------------|

¹⁾ Halogen lamp

Certificates & standards

| | |
|--------------|----|
| ECE category | H4 |
|--------------|----|

Country specific categorizations

| | |
|-----------------|------------|
| Order reference | 64193NB220 |
|-----------------|------------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|---|
| Date of Declaration | 21-06-2024 |
| Primary Article Identifier | 4062172399449 4062172399395 4062172399531 4062172399555 |
| Declaration No. in SCIP database | In work |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|----------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172399449 | NIGHT BREAKER 220 H4 | Folding carton box 1 | 47 mm x 47 mm x 71 mm | 0.16 dm ³ | 29.00 g |
| 4062172399456 | NIGHT BREAKER 220 H4 | Bundle 10 | 235 mm x 94 mm x 71 mm | 1.57 dm ³ | 296.00 g |
| 4062172399463 | NIGHT BREAKER 220 H4 | Shipping carton box 100 | 485 mm x 250 mm x 160 mm | 19.40 dm ³ | 3213.00 g |
| 4062172399555 | NIGHT BREAKER 220 H4 | HFB 2 | 100 mm x 51 mm x 120 mm | 0.61 dm ³ | 72.00 g |
| 4062172399562 | NIGHT BREAKER 220 H4 | Shipping carton box 10 | 266 mm x 111 mm x 134 mm | 3.96 dm ³ | 437.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Light output compared to the minimum ECE R112/R37 requirements

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM