

XENARC NIGHT BREAKER 220



Up to 220% more brightness¹⁾ Compared to minimum ECE R98/R99 requirements

More light allows to see farther and therefore react sooner compared to the minimum legal standard



Up to 250 m long beam

For better visibility



Up to 220% more brightness¹⁾ Compared to minimum ECE R98/R99 requirements

More modern look compared to the minimum legal standard



The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
XENARC NIGHT BREAKER 220 D1S	35 W	85 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D2S	35 W	85 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D3S	35 W	42 V	35 W	13.5 V	3200 lm
XENARC NIGHT BREAKER 220 D4S	35 W	42 V	35 W	13.5 V	3200 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions		Lifetime Data		Capabilities
		Diameter	Diameter	Lifespan B3	Lifespan Tc	Technology
XENARC NIGHT BREAKER 220 D1S	±15 %	9 mm	9 mm	1500 hr	3000 hr	HID ¹⁾
XENARC NIGHT BREAKER 220 D2S	±15 %	9 mm	9 mm	1500 hr	3000 hr	HID ¹⁾
XENARC NIGHT BREAKER 220 D3S	±15 %	9 mm	9 mm	2000 hr	3000 hr	HID ¹⁾
XENARC NIGHT BREAKER 220 D4S	±15 %	9 mm	9 mm	2000 hr	3000 hr	HID ¹⁾

Product description	Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	ECE category	Primary article identifier	Candidate list substance 1	CAS No. of substance 1
XENARC NIGHT BREAKER 220 D1S	D1S ²⁾	4062172398619 4062172397735	Lead	7439-92-1
XENARC NIGHT BREAKER 220 D2S	D2S ²⁾	4062172398640 4062172397766		
XENARC NIGHT BREAKER 220 D3S	D3S ²⁾	4062172398671 4062172397797	Lead	7439-92-1
XENARC NIGHT BREAKER 220 D4S	D4S ²⁾	4062172398701 4062172397827		

Product description	Safe use instruction	Declaration no. in SCIP database
XENARC NIGHT BREAKER 220 D1S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0682beb0-fcb6-4643-b1bf-f0df283c2352 5a5302eb-4799-4cbd-a466-1a125eac6e0a
XENARC NIGHT BREAKER 220 D2S		In work
XENARC NIGHT BREAKER 220 D3S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2322ca85-73dd-494d-97a0-7d1ae5c23717 3dea30b6-ada1-419d-b9db-7582b1c7f8bf
XENARC NIGHT BREAKER 220 D4S		In work

Product family datasheet

¹⁾ High-intensity discharge lamp

²⁾ To be operated only with approved electronic control gear

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	ref_pim_amsproduct360degreeimages XENARC ORIGINAL D1S 66140
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D2S 66240XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D3S 66340XNB
	ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D4S 66440XNB

Safety advice

XENARC lamps should be replaced by a qualified mechanicThis product must only be operated with approved electronic control gear

Legal advice

Light output compared to the minimum ECE R112/R37 requirementsThis product must only be operated with approved electronic control gearXENARC lamps should be replaced by a qualified mechanicReduced UV emission | For projection headlights | ECE approval and DOT label± 450 lm

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.